

**Amendments to the Claims:**

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) An input device including:

a foldable keyboard including a first keyboard unit, a second keyboard unit, and a rotatable connecting part provided between the first and second keyboard units, so that the first and second keyboard units are rotated relative to a first axis to come apart from each other into an unfolded, horizontally arranged state through the connecting part for use of the keyboard, while the first and second keyboard units are rotated relative to the first axis to come close to each other into a closed, folded state through the connecting part for nonuse of the keyboard, and

a foldable flexible display rotatably attached to one edge of the first or second keyboard unit in order to rotate relative to a second axis, the display being openable relative to a support point when the first and second keyboard units are in the horizontally arranged state and foldable relative to the support point when the first and second keyboard units are in the folded state, wherein the second axis and the support point are not at a same ~~location~~ location, wherein the foldable flexible display includes a flexible display sheet that bends when the foldable flexible display is folded relative to the support point.

2. (Currently Amended) The input device according to claim 1, wherein the flexible display includes:

a first cover member rotatably attached to one edge of the first or second keyboard unit;

a second cover member provided side by side with the first cover member along a long side of the opened keyboard in which the first and second keyboard units are horizontally arranged;

a joint provided between the first and second cover members; and  
a linkage system integrally formed with the joint at both ends thereof, the linkage system including a pair of link parts which couples the first and second cover members; and members;

~~a flexible~~ wherein the flexible display sheet is placed over the first cover member, the joint, and the second cover member,

the second cover member being slidable and foldable through the linkage system with respect to the first cover member.

3. (Original) The input device according to claim 2, wherein the flexible display is attached to one edge of the first or second keyboard unit so that the display is arranged along a direction perpendicular to an axis of the rotatable connecting part.

4. (Original) The input device according to claim 2, further including:  
a pair of first wall portions provided in peripheral opposite edges of the first cover member;  
a first groove formed in an inner surface of each first wall portion;  
a pair of second wall portions provided in peripheral opposite edges of the second cover member;  
a second groove formed in an inner surface of each second wall portion;  
wherein both side edges of the flexible display sheet are slidably held in one of the first and second grooves.

5. (Original) The input device according to claim 2, wherein the flexible display sheet is folded to cover from outside both surfaces of the keyboard in which the first and second keyboard units are superposed when the second cover member is folded on the first cover member.

6. (Original) The input device according to claim 5, wherein the joint includes a semicylindrical body having a semicylindrical curved surface, and  
the flexible display sheet is folded as partially curved along the semicylindrical curved surface when the second cover member is folded on the first cover member.

7. (Original) The input device according to claim 2, wherein the flexible display sheet is an organic electroluminescence (EL) display sheet.

8. (Currently Amended) A personal computer including:  
a foldable keyboard including a first keyboard unit, a second keyboard unit, and a rotatable connecting part provided between the first and second keyboard units, so that the first and second keyboard units are rotated relative to a first axis to come apart from each other into an unfolded, horizontally arranged state through the connecting part for use of the keyboard, while the first and second keyboard units are rotated relative to the first axis to come close to each other into a closed, folded state through the connecting part for nonuse of the keyboard, and

a computer main unit provided to the first or second keyboard unit; and

a foldable flexible display rotatably attached to one edge of the first or second keyboard unit in order to rotate relative to a second axis, the display being openable relative to a support point when the first and second keyboard units are in the horizontally arranged state and foldable relative to the support point when the first and second keyboard units are in the folded state, wherein the second axis and the support point are not at a same ~~location~~.  
location, wherein the foldable flexible display includes a flexible display sheet that bends when the foldable flexible display is folded relative to the support point.

9. (Currently Amended) The personal computer according to claim 8, wherein the flexible display includes:

a first cover member rotatably attached to one edge of the first or second keyboard unit;

a second cover member provided side by side with the first cover member along a long side of the opened keyboard in the horizontally arranged state of the first and second keyboard units;

a joint provided between the first and second cover members; and

a linkage system integrally formed with the joint at both ends thereof, the linkage system including a pair of link parts which couples the first and second cover ~~members; and~~ members;

~~a flexible~~ wherein the flexible display sheet is placed over the first cover member, the joint, and the second cover member,

the second cover member being slidable and foldable through the linkage system with respect to the first cover member.

10. (Original) The input device according to claim 1, wherein a resilient metallic thin plate is laminated to a rear surface of the flexible display.

11. (Original) The input device according to claim 10, wherein the flexible display includes:

a first cover member rotatably attached to one edge of the first or second keyboard unit and a second cover member slidably and foldably connected with the first cover member; and

a flexible display sheet placed over the first cover member and the second cover member, and

the resilient metallic thin plate is laminated to the flexible display sheet on a surface facing the first and second cover members.

12. (Original) The personal computer according to claim 8, wherein

a resilient metallic thin plate is laminated to a rear surface of the flexible display.

13. (Original) The input device according to claim 1, wherein  
the flexible display includes: a cover unit having a length longer than the first or second keyboard unit; and a flexible display sheet set in the cover unit; and  
the cover unit includes: a support portion formed at a lower end for rotatably supporting the cover unit in a cantilever state at one edge of the first or second keyboard unit; and a projection member formed at another lower end opposite to the end formed with the support portion so that a bottom surface of the projection member is flush with a bottom surface of the opened keyboard.

14. (Original) The input device according to claim 13, wherein the support portion of the cover unit is connected with the one edge of the first or second keyboard unit along a direction perpendicular to an axis of the connecting part.

15. (Original) The input device according to claim 13, wherein  
the cover unit includes:  
a first cover member provided with a support portion and rotatably attached to the one edge of the first or second keyboard unit through the support portion;  
a second cover member provided side by side with the first cover member along a long side of the opened keyboard in the horizontally arranged state of the first and second keyboard units; and  
a joint provided between the first and second cover members to connect the first and second cover members in a slidable and foldable relation; and  
the projection member is formed at a lower part of the second cover member.

16. (Original) The input device according to claim 15, wherein the flexible display sheet is folded to cover from outside both surfaces of the keyboard which the first and

second keyboard units are superposed when the second cover member is folded on the first cover member.

17. (Original) The input device according to claim 15, wherein the joint includes a semicylindrical body having a semicylindrical curved surface, and

the flexible display sheet is folded as partially curved along the semicylindrical curved surface when the second cover member is folded on the first cover member.

18. (Previously Presented) A personal computer including:

a foldable keyboard including a first keyboard unit, a second keyboard unit, and a rotatable connecting part provided between the first and second keyboard units, so that the first and second keyboard units are rotated to come apart from each other into an unfolded, horizontally arranged state through the connecting part for use of the keyboard, while the first and second keyboard units are rotated to come close to each other into a closed, folded state through the connecting part for nonuse of the keyboard, and

a computer main unit provided to the first or second keyboard unit; and

a foldable flexible display including a cover unit having a length longer than the first or second keyboard unit and a flexible display sheet set in the cover unit, the cover unit including a support portion at a lower end for rotatably supporting the cover unit in a cantilever state at one edge of the computer main unit so that the display is openable when the first and second keyboard units are in the horizontally arranged state and foldable when the first and second keyboard units are in the folded stated,

wherein the cover unit further includes a projection member formed at another lower end opposite to the end formed with the support portion so that a bottom surface of the projection member is flush with a bottom surfaces of the opened keyboard and the computer main unit.

19. (Original) The input device according to claim 1, wherein the flexible display is widened from the folded state to a state extending in a direction parallel to a long side of the keyboard in which the first and second keyboard units are horizontally arranged.

20. (Original) The input device according to claim 19, wherein the keyboard has a first length in the horizontally arranged state of the first and second keyboard units, and the flexible display includes a display part having a length substantially equal to the first length, and the flexible display is folded, due to the flexibility, to another length substantially equal to a second length of the folded keyboard in which the first and second keyboard units are superposed one on top of the other through the connecting part.

21. (Original) The input device according to claim 19 further including a control unit united with the first or second keyboard unit and used for controlling the keyboard and the flexible display, wherein the flexible display is rotatably attached to one edge of the control unit and has a width corresponding to a total width of the first or second keyboard unit and the control unit.

22. (Original) The personal computer according to claim 8, wherein the flexible display is widened from the folded state to a state extending in a direction parallel to a long side of the keyboard in which the first and second keyboard units are horizontally arranged.

23. (Original) The personal computer according to claim 22, wherein the keyboard has a first length in the horizontally arranged state of the first and second keyboard units, and the flexible display includes a display part having a length substantially equal to the first length and is folded, due to the flexibility, to another length substantially equal to a second length of the keyboard in which the first and second keyboard units are superposed one on top of the other through the connecting part.

24. (Original) The personal computer according to claim 22, wherein the flexible display is folded to cover from outside both surfaces of the keyboard in which the first and second keyboard units are superposed one on top of the other.

25. (Original) The personal computer according to claim 22, wherein the flexible display has a width corresponding to a total width of the first or second keyboard unit and the control unit.

26. (Original) The input device according to claim 1, wherein the keyboard has a first length in the horizontally arranged state of the first and second keyboard units, and the flexible display includes a display part having a length substantially equal to the first length and is folded, due to the flexibility, to another length substantially equal to a second length of the keyboard in which the first and second keyboard units are superposed one on top of the other through the connecting part.

27. (Original) The input device according to claim 1, wherein the first and second keyboard units each are of a rectangular shape having long sides and short sides, and the flexible display is folded along the long sides.

28. (Original) The input device according to claim 27, wherein the keyboard in which the first and second keyboard units are horizontally arranged has an open length in parallel to the long side of the keyboard unit, and the flexible display includes a landscape display part having a length substantially equal to the open length of the keyboard, and the flexible display is folded, due to the flexibility, to another length substantially equal to a length of the long side of the folded keyboard in which the first and second keyboard units are superposed through the connecting part.

29. (Original) The input device according to claim 27 further including



a control unit united with the first or second keyboard unit and used for controlling the keyboard and the flexible display,

wherein the flexible display is rotatably attached to one edge of the control unit and has a width corresponding to a total width of the first or second keyboard unit and the control unit in a direction of the short side.

30. (Original) The input device according to claim 1, the first and second keyboard units each are of a rectangular shape having long sides and short sides, and the flexible display is folded along the short sides.

31. (Original) The input device according to claim 30 further including a control unit united with the first or second keyboard unit and used for controlling the keyboard and the flexible display, wherein the flexible display is rotatably attached to one edge of the control unit and includes a portrait display part having a width substantially equal to the length of the long side of the folded keyboard in which the first and second keyboard units are superposed, so that the flexible display is folded to another width substantially equal to a total width of the first or second keyboard unit and the control unit in a direction of the short side.

32. (Original) The input device according to claim 1, wherein the flexible display is folded to cover from outside both surfaces of the keyboard in which the first and second keyboard units are superposed.

33. (Currently Amended) A display including:

a first cover member;

a second cover member provided side by side with the first cover member;

a joint provided between the first and second cover members;

a linkage system integrally formed with the joint at both ends thereof, the linkage system including a pair of link parts which couples the first and second cover members; and

a flexible display sheet placed over the first cover member, the joint, and the second cover member,

the second cover member being slidable and foldable through the linkage system with respect to the first cover member, wherein the second cover member is slidable with respect to the first cover member when the first and second cover members are positioned in the same plane.

34. (New) An input device including:

a foldable keyboard including a first keyboard unit, a second keyboard unit, and a rotatable connecting part provided between the first and second keyboard units, so that the first and second keyboard units are rotated relative to a first axis to come apart from each other into an unfolded, horizontally arranged state through the connecting part for use of the keyboard, while the first and second keyboard units are rotated relative to the first axis to come close to each other into a closed, folded state through the connecting part for nonuse of the keyboard, and

a foldable flexible display rotatably attached to one edge of the first or second keyboard unit in order to rotate relative to a second axis, the display being openable relative to a support point when the first and second keyboard units are in the horizontally arranged state and foldable relative to the support point when the first and second keyboard units are in the folded state, wherein the second axis and the support point are not at a same, and wherein the foldable, flexible display includes:

a first cover member rotatably attached to one edge of the first or second keyboard unit;

a second cover member positioned side by side along a long side of the opened keyboard in which the first and second keyboard units are horizontally arranged when the display is in an open state;

a joint provided between the first and second cover members; and

a flexible display sheet disposed on one side of the first and second cover members, and traversing the joint.

35. (New) The input device according to claim 34, wherein the foldable, flexible display is foldable in a direction such that the display sheet opposes itself when the display is in a folded state.